

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 1

Substance key: SXR024811
Version : 2 - 10 / USARevision Date: 11/25/2011
Date of printing :06/19/2014**Section 01 - Product and company identification****Identification of the company:**Clariant Corporation
4000 Monroe Road
Charlotte, NC, 28205
Telephone No.: +1 704 331 7000**Information of the substance/preparation:**

Product Safety 1-704-331-7710

Emergency tel. number: +1 800-424-9300 CHEMTREC**Trade name:** **POLYGLYKOL 1500 S****Material number:** 105258**CAS number:** 25322-68-3**Synonyms:** Product Has No Synonyms**Primary product use:** Techno-chemical industry.
Syntheses
Cosmetic
Pharma**Primary product use:** Carrier substance**Chemical family:** Polyethylene glycol [HO-(CH₂-CH₂-O)_n-H, average molecular mass = 1500]**Section 02 - Hazards identification****Emergency overview:**White flakes.
May cause dust explosions.
May cause irritation.**Expected Route of entry:****Inhalation:**

Particulates of this material are probably irritating to respiratory passages, nose, and throat.

Skin contact:

May cause mild skin irritation.

Eye contact:

May cause mild eye irritation

Ingestion:

Not expected to be toxic.

Skin absorption:

no

Health effects of exposure:

Particulates Not Otherwise Regulated (PNOR)

Although this substance did not cause irritation in standard skin and eye irritation studies, particulates of this material may cause mechanical irritation to the skin, eye or respiratory tract.

Known effects on other illnesses:

No known effects on other illnesses for this product.

Listed carcinogen:IARC: No
NTP: No
OSHA: No

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 2

Substance key: SXR024811
Version : 2 - 10 / USARevision Date: 11/25/2011
Date of printing :06/19/2014

Other: No

HMIS:

Health: 1

Flammability: 1

Reactivity: 0

Personal protection: E

Section 03 - Composition/information on ingredients**Hazardous ingredients:**

Component	CAS-no. (Trade secret no.)	Concentration
Polyethylene glycol	25322-68-3	<= 100 %

Section 04 - First aid measures**After inhalation:**

Get victim to fresh air. Give artificial respiration or oxygen if breathing has stopped. Get prompt medical attention. Do not give fluids if victim is unconscious.

After contact with skin:

Immediately flush skin under running water for at least fifteen minutes. Seek medical attention if irritation or chemical burn is present.

After contact with eyes:

Immediately flush eyes with running water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek prompt medical attention if redness or irritation occurs.

After ingestion:

If victim is conscious, give large amounts of water or milk. Consult a physician. Never give anything by mouth to an unconscious person.

Advice to doctor / Treatment:

None known.

Section 05 - Fire fighting measures

Flashpoint:	518 °F Method: DIN 51376 (open cup)
Lower explosion limit:	Not applicable
Upper explosion limit:	Not applicable
Self ignition:	not tested.
Ignition temperature:	> 608 °F Method: DIN 51794

Hazardous combustion products:

In case of fires, hazardous combustion gases are formed: Carbon monoxide (CO)
Carbon dioxide (CO₂)

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 3

 Substance key: SXR024811
 Version : 2 - 10 / USA

 Revision Date: 11/25/2011
 Date of printing :06/19/2014

Extinguishing media: water spray jet
dry powder
foam
carbon dioxide

Special fire fighting procedure:
Exercise caution when fighting any chemical fire. Use NIOSH approved self-contained breathing apparatus and full protective clothing.

Unusual fire and explosion hazards: Emits toxic fumes under fire conditions.

Organic dusts have potential to be explosive with static spark or flame initiation. Maintain good housekeeping for control of dust. Ground all containers when transferring to avoid static charges.

Section 06 - Accidental release measures
Steps to be taken in case of spill or leak:

Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak. Collect onto inert absorbent. Place in suitable container.

Section 07 - Handling and storage
Advice on safe handling:

Store in a cool dry location. Do not breathe dust. Do not get in eyes or on skin. Wear proper protective equipment. Keep container tightly closed.

Avoid dust formation. Keep away from sources of ignition. Lead off electrostatic charges.

Further info on storage conditions:

Store in original container.

Keep containers closed.

Do not keep at temperatures above 30 °C.

Recommended storage temperature: 10 - 25 °C.

Section 08 - Exposure controls / personal protection
Occupational exposure limits:

Component	CAS number:	Regulatory list	Type of value	Values / Remarks
Polyethylene Glycols (MW > 200)	25322-68-3	AIHA. Workplace Environmental Exposure Levels (WEEL)	Time-weighted average (8 hrs)	10 mg/m ³
PARTICULATES NOT OTHERWISE REGULATED RESPIRABLE FRACTION		US OSHA Table Z-1 Limits for Air Contaminants [29 CFR 1910.1000]	8-hour Time Weighted Averages	5 mg/m ³
PARTICULATES NOT OTHERWISE REGULATED TOTAL DUST		US OSHA Table Z-1 Limits for Air Contaminants [29 CFR 1910.1000]	8-hour Time Weighted Averages	15 mg/m ³

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 4

Substance key: SXR024811
Version : 2 - 10 / USARevision Date: 11/25/2011
Date of printing :06/19/2014

Respiratory protection:	If airborne concentrations pose a health hazard, become irritating or exceed recommended limits, use a NIOSH approved respirator in accordance with OSHA respiratory protection requirements under 29 CFR 1910.134
Hand protection:	Butyl Rubber, PVC Or Neoprene.
Eye protection:	Safety glasses or chemical splash goggles.
Other protective equipment:	Protective clothing to minimize skin contact should be worn. Chemically resistant safety shoes. Wash contaminated clothing with soap and water and dry before reuse. Safety showers and eyewash stations should be provided in all areas where this material is handled.
Advice on system design:	Where a closed system is not used, good enclosure and local exhaust ventilation should be provided.
IDLH:	None

Section 09 - Physical and chemical properties

Form:	Flakes
Color:	white
Odor:	odourless
Odor limit:	not tested.
pH:	5 - 7 (20 °C, 100 g/l) Method: DIN 19268
Solubility in water:	approx. 500 g/l (20 °C)
Soluble in ... :	fat not tested.
Density:	1.1 - 1.12 g/cm ³ (25 °C) Method: DIN 51757
Freezing point :	111 - 118 °F Method: European Pharmacopoeia / 2.2.18
Boiling temperature :	not determined
Vapor pressure:	< 0.01 Torr (20 °C)
Bulk density:	400 - 500 kg/m ³
Relative vapor density:	
Partitioning coef. octanol/water:	< -1
Viscosity / (dynamic):	36 - 42 mPa.s (20 °C) Method: DIN 53019 50 % aqueous solution

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 5

Substance key: SXR024811
Version : 2 - 10 / USARevision Date: 11/25/2011
Date of printing :06/19/2014

Viscosity / (kinematic): 33 - 39 mm²/s (20 °C)
Method: DIN 51562
50 % aqueous solution

Section 10 - Stability and reactivity

Thermal decomposition: 360 °C
Source: Analogy

Chemical stability: Under normal conditions the product is stable.

Hazardous Polymerization: Will not occur.

Conditions to avoid: Keep away from heat, sparks, and open flame.

Section 11 - Toxicological information

Product information:

Acute oral toxicity: LD50 > 15,000 mg/kg (rat)

Acute inhalation toxicity: not tested.

Acute dermal toxicity: not tested.

Skin irritation: Non-irritating (rabbit)

Eye irritation: Non-irritating (rabbit)

Other relevant toxicity information:
By analogy with a product of similar composition

Section 12 - Ecological information

Product information:

Biodegradation: > 95 % (26 d)
good degradability
Method: DIN 38412 T.24

Fish toxicity: LC50 > 10 g/l (48 h, golden orfe)
Method: DIN 38412 T.15
Source: Analogy

Daphnia toxicity: not tested.

Algae toxicity: not tested.

Bacteria toxicity: EC50 > 1,000 mg/l (3 h)
Method: OECD 209

Chemical oxygen demand (COD): 1,800 mg/g
Method: DIN 38409-H41

Remarks:
No data available.

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 6

Substance key: SXR024811
Version : 2 - 10 / USARevision Date: 11/25/2011
Date of printing :06/19/2014**Section 13 - Disposal considerations****Waste disposal information:**

Recommended disposal is by incineration in approved facilities.

RCRA hazardous waste:

No -- Not as sold.

RCRA number: NONE

Section 14 - Transport information

DOT	not restricted
IATA	not restricted
IMDG	not restricted

Section 15 - Regulatory information**TSCA Status:**

All components of this product are listed on the TSCA Inventory.

SARA (section 311/312):

Reactive hazard:	no
Pressure hazard:	no
Fire hazard:	yes
Immediate/acute:	yes
Delayed/chronic:	no

SARA 313 information:

This product does not contain any toxic chemical listed under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986.

Clean Water Act:

Contains no known priority pollutants at concentrations greater than 0.1%.

Volatile organic compounds VOC:

Remarks: Not Available

FDA:

FDA regulated cosmetic ingredient.

MATERIAL SAFETY DATA SHEET
POLYGLYKOL 1500 S

Page 7

Substance key: SXR024811
Version : 2 - 10 / USA

Revision Date: 11/25/2011
Date of printing :06/19/2014

Section 16 - Other information**Other precautions:**

None Known

Label information:

WARNING!

MAY CAUSE SKIN, EYE OR RESPIRATORY TRACT IRRITATION DUST
EXPLOSION HAZARD

Avoid breathing dust. Wear NIOSH approved respiratory protection when handling this product. Avoid contact with skin, eyes and clothing. Avoid ingestion. Wear proper protective equipment. Wash thoroughly after handling. Keep container closed when not in use.

In case of EYE CONTACT, flush with water for 15 minutes while holding eyelids open. SKIN CONTACT: Wash thoroughly with soap and water. Seek medical attention if irritation occurs. For inhalation, remove to fresh air, consult a physician. Ingestion: If conscious, give the patient 1 - 2 glasses of water (8 - 16 oz.). Induce vomiting only at the instructions of a doctor or nurse.

This information is supplied under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and is offered in good faith based on data available to us that we believe to be true and accurate. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable to the material. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate for that use. No warranty, express or implied, is made regarding the accuracy of this data, the hazards connected with the use of the material, or the results to be obtained from the use thereof. We assume no responsibility for damage or injury from the use of the product described herein. Data provided here are typical and not intended for use as product specifications.