



Technical Data Sheet

PELLET LUBE F3 DRUM

Technical Name: Pellet Lube F3
CAS #:
Appearance: Tan viscous slurry/ Mild odor

Technical Parameters:	Min	Max
Specific Gravity	1.398	1.522
PH of Concentrate	9.8	10.2

Typical properties not reported on the COA;
Average Solids Content % 55

Stability of Concentrate - will not settle

Special Handling Instruction: Keep from freezing

This material is high solids slurry formulated as an antitack coating for various rubber substrates. Pellet LubeF3 is especially formulated to dry quickly and provide a barrier film that will not be worn off as the pellets are conveyed and/or tumbled.

The above information has been compiled from what we believe to be credible sources. To our knowledge the information is accurate and reliable, however, it is not guaranteed. Any recommendations issued by HB Chemical personnel or literature is derived from experience and by no means should be taken as fact or construed as a recommendation to violate of any law, regulation or patent. It is the users responsibility to determine the suitability of any HB supplied material in their application. The individual conditions of each customer are well outside of our control and we cannot be held liable for its functionality and use. Please contact our office should you need specific information beyond what is supplied above. As with all Chemical usage safety precautions beyond the stated are highly recommended.

1665 ENTERPRISE PARKWAY, TWINSBURG, OH, 44087 Tel: (330) 920-8023 Fax: (330) 920-0971